



City of
Los Banos
At the Crossroads of California

ADDENDUM NO. 1

October 13, 2017

PROPOSAL FOR THE PURCHASE OF ONE NEW 2017/2018 MODEL VACUUM STREET SWEEPER

City of Los Banos
Public Works Department
411 Madison Avenue
Los Banos, CA 93635
(209) 827-7056

Mark Fachin P.E.
Public Works Director/ City Engineer

Bidders are hereby informed that the Bid Specifications for the above referenced proposal have been modified, corrected, and/or supplemented.

The following section shall replace the same named section in the Bid Specifications: Specifications Compliance. An Addendum Acknowledgment page has been added. The modified pages must be submitted with the Bid Proposal forms. Additions/revisions are shown in italic and are underlined; deletions are shown with strikethrough.

Any Proposal submitted without the modified page shall be considered non-responsive and shall be rejected.

Specifications Compliance - Continued

Yes No Each line specification requires checking either the Yes or No box

AUXILIARY ENGINE

- John Deere 4045T tier 4 final (or equivalent).
- Remote engine fluid drain accessible from ground level coolant, engine oil, hydraulic oil and gear box oil.
- Enclosed engine compartment with access doors.
- Automatic shutdown system for low oil pressure and over temperature protection.
- LED lights in engine compartment.

BLOWER

- The blower needs to generate the necessary airflow to convey the debris from the suction nozzle into the hopper and vacuum needed to overcome any restrictions such as rocks or bulky debris.

SUCTION NOZZLES

- Dual 30 (minimum) abrasion resistant suction nozzles.
- Tilt nozzle from cab to allow easy entry of larger debris.

GUTTER BROOMS

- Gutter brooms and components shall be free floating, of trailing arm design with inward motion to prevent damage when sweeping and encountering a fixed obstacle.
- Adjustable down pressure controlled from cab.
- Pneumatically raise and lower.
- Gutter brooms to be held in place by a positive means of support during transport.
- Side broom tilt or rotation controlled from cab.
- ~~One pallet of gutter brooms for sweeper.~~
Shall read one pallet of side gutter brooms for sweeper (16 sets minimum).
- Gutter broom speed control from cab.
- Automatic pickup in reverse gear of all sweeping equipment.
- A preprogrammed sweep setting or memory sweep (or equivalent).

HYDRAULIC SYSTEM

- Hydraulic tank capacity 20 gallons (minimum) and have a exterior sight glass.
- Hydraulic cooler to provide adequate cooling for demand.
- Filter shall be accessible from ground level for easy service.

THIS PAGE MUST BE COMPLETED AND RETURNED WITH THE BID PROPOSAL

ADDENDUM NO. 1

Addendum Acknowledgement

Bidder acknowledges receipt of the following Addenda:

No. 1, dated October 13, 2017 Signed, _____

THIS PAGE MUST BE COMPLETED AND RETURNED WITH THE BID PROPOSAL

ADDENDUM NO. 1